This article needs some TLC. Read at your own risk.

SuFami Turbo

The SuFami Turbo is an accessory released by Bandai for Nintendo's Super Famicom system and was released in 1996, retailing for ¥7,980 JPY.

The unit would be inserted into the Super Famicom and offer its own two separate cartridge slots. The idea being that not having to rely on Nintendo to manufacture expensive cartridges for game distribution would cut down on the costs of game distribution. The product itself was officially endorsed by Nintendo, under the condition that Bandai would handle all aspects of hardware manufacturing itself.

The dual slot design would allow multiple games to communicate with each other, the idea for the game in slot 1 to be the one that's currently being played and the game in slot 2 being the one providing additional data for the game currently being played. Of the thirteen games released for the SuFami Turbo, nine of them can link up.

This system scrapes metadata for the "sufami" group and loads the `sufami` set from the currently selected theme, if available.

Grouped with the "snes" group of systems.

Quick reference

- **Emulator:** RetroArch
- **Core:** libretro: snes9x
- **Folder:** /userdata/roms/sufami
- **Accepted ROM formats:** .st, .fig, .bs, .smc, .sfc, .zip, .7z

BIOS

MD5 checksum	Share file path	Description
d3a44ba7d42a74d3ac58cb9c14c6a5ca	bios/STBIOS.bin	

ROMs

Place your SuFami Turbo ROMs in /userdata/roms/sufami.

Emulators

RetroArch

RetroArch (formerly SSNES), is a ubiquitous frontend that can run multiple "cores", which are essentially the emulators themselves. The most common cores use the libretro API, so that's why cores run in RetroArch in Batocera are referred to as "libretro: (core name)". RetroArch aims to unify the feature set of all libretro cores and offer a universal, familiar interface independent of platform.

RetroArch configuration

RetroArch offers a **Quick Menu** accessed by pressing [HOTKEY] + which can be used to alter various things like RetroArch and core options, and controller mapping. Most RetroArch related settings can be altered from Batocera's EmulationStation.

Standardized features available to all libretro cores: `sufami.videomode`, `sufami.ratio`, `sufami.smooth`, `sufami.shaders`, `sufami.pixel_perfect`, `sufami.decoration`, `sufami.game_translation`

| ES setting name batocera.conf_key	Description ⇒ ES option key_value
Settings that apply to all cores of this emulator	
GRAPHICS API `sufami.gfxbackend`	Choose which graphics API library to use. Vulkan is better, when supported. ⇒ OpenGL `opengl`, Vulkan `vulkan`.
AUDIO LATENCY `sufami.audio_latency`	In milliseconds. Can reduce crackling/cutting out. ⇒ 256 `256`, 192 `192`, 128 `128`, 64 `64`, 32 `32`, 16 `16`, 8 `8`.
THREADED VIDEO `sufami.video_threaded`	Improves performance at the cost of latency and more video stuttering. ⇒ On `true`, Off `false`.

libretro: snes9x

libretro: snes9x configuration

ES setting name batocera.conf_key	Description ⇒ ES option key_value
Settings that apply to all systems this core supports	
REDUCE SPRITE FLICKERING (UNSTABLE) `global.reduce_sprite_flicker`	Enhancement. Remove the thirty-two sprites per line limit. Crashes certain games. ⇒ Off `disabled`, On `enabled`.
OVERCLOCK (UNSTABLE) `global.reduce_slowdown`	Overclock the SNES CPU (Gradius 3, Super R-Type). ⇒ Off `disabled`, Light (load times) `light`, Compatible `compatible`, Max (demanding games) `max`.

ES setting name batocera.conf_key	Description ⇒ ES option key_value
SUPER FX OVERCLOCK `global.overclock_superfx`	Enhancement. Reduces slowdown in mode 7 games. ⇒ 50% `50%`, 60% `60%`, 70% `70%`, 80% `80%`, 90% `90%`, 100% `100%`, 150% `150%`, 200% `200%`, 250% `250%`, 300% `300%`, 350% `350%`, 400% `400%`, 450% `450%`, 500% `500%`.
BLEND HIGH-RES MODE `global.hires_blend`	Blur high-res mode, allowing for better transparency effects. ⇒ Off `disabled`, Merge `merge`, Blur `blur`.
CONTROLLER 1 TYPE `global.controller1_snes9x`	⇒ SNES Gamepad 1, SNES Mouse 2.
CONTROLLER 2 TYPE `global.controller2_snes9x`	Lightguns can only be used in port 2. ⇒ SNES Gamepad 1, SNES Mouse 2, SNES Multitap 257, Super Scope 260, Konami Justifier 516, M.A.C.S. Rifle 1028.
CONTROLLER 3 TYPE `global.controller3_snes9x`	Konami Justifier P2 is daisy chained from controller 2, appears as port 3 to system. ⇒ SNES Gamepad 1, Konami Justifier (P2) 772.

Controls

Here are the default SuFami Turbo's controls shown on a Batocera Retropad:

Troubleshooting

Further troubleshooting

For further troubleshooting, refer to the generic support pages.